



BB CHRYSLER INTERNAL BYPASS FUEL PUMP KITS (COMPLETE)

7462R FUEL PUMP KIT - INTERNAL BYPASS

BB Chrysler with RH mount location 10 o'clock inboard position. Available in .400, .500 and .600 wide gear configuration.

NOTE: This kit works only with the factory Chrysler water pump.

KIT COMPONENTS	QTY	DESCRIPTION
7448	1	RH 10 o'clock mount bracket
322L050	1	32.2" x .500" 3/8 pitch drive belt
7103-14L050	1	14th x .500 drive gear steel
7013-2.250	2	Belt guard washers
7150	1	28th x .500 upper drive pulley
7400	1	RH Internal bypass fuel pump

NOTE: Drive mandrel not included, must be ordered separate.

BB CHRYSLER EXTERNAL BYPASS FUEL PUMP KIT - RETURN LINE REQUIRED


7362R FUEL PUMP KIT - RETURN LINE REQUIRED

BB Chrysler with RH mount location 10 o'clock inboard position. Available in .400, .500 and .600 wide gear configuration.

NOTE: This kit works only with the factory Chrysler water pump.

KIT COMPONENTS	QTY	DESCRIPTION
7448	1	RH 10 o'clock mount bracket
322L050	1	32.2" x .500" 3/8 pitch drive belt
7103-14L050	1	14th x .500 drive gear steel
7013-2.250	2	Belt guard washers
7150	1	28th x .500 upper drive pulley
7399	1	RH External bypass fuel pump

NOTE: Drive mandrel not included, must be ordered separate.



FUEL PUMP PULLEYS, DRIVE GEARS AND DRIVE MANDRELS

Pulleys are hard coated for long life. The fuel pump pulleys have a belt guard installed.

PART NO.	DESCRIPTION
7103-14L050	14 tooth .500" wide steel drive gear.
7103-16L050	16 tooth .500" wide aluminum drive gear.
7150	28-tooth .500" wide fuel pump pulley.
7151	32-tooth .500" wide fuel pump pulley.

NOTE: Fuel pump drive mandrels can be found on page 48.



MOUNTING BRACKETS

Fuel pump mounting bracket comes with aluminum spacers and mounting bolts.

PART NO.	DESCRIPTION
7429	B/B Chevy, RH low mount. Use belt 270L050.
7440	S/B Chevy 10 o'clock position right hand mount. This mount moves the fuel pump inboard close to the water pump. Use belt 300L050.
7441	S/B Chevy 9 o'clock position right hand mount. designed for circle track engines using a fan blade. It moves the fuel pump outboard and back toward the head for more fan blade clearance. Use belt 322L050.
7442R	S/B Chevy RH low mount that bolts to the 2 lower 3/8 x 16 holes in the front of the block. Use belt 240L050.
7442L	S/B Chevy LH low mount that bolts to the 2 lower 3/8 x 16 holes in the front of the block. Use belt 225L050.
7443	S/B and B/B left hand mount designed to bolt to the Moroso self contained water pump. Use belt 285L050.
7444R	B/B Chevy RH 10 o'clock position. The mount moves the fuel pump inboard close to the water pump. Use belt 300L050.
7444L	B/B Chevy LH 2 o'clock position. The mount moves the fuel pump inboard close to the water pump. Use belt 285L050.
7381	S/B Chevy right hand mount to use an Enderle fuel pump (requires a 7146 idler bracket). Use belt 345L050.
7445R	S/B Ford mount, right hand side. Use belt 300L050.
7445L	S/B Ford mount, left hand side. Use belt 300L050.
7446	B/B Ford RH side mount. Use belt 285L050.
7448	B/B Chrysler RH side mount. Use belt 322L050.
7483	B/B Chevy left hand low mount that mounts in close to the crankshaft. Use belt 225L050.

FUEL PUMP DRIVE BELTS

PART NUMBER	LENGTH	NO. OF TEETH	PART NUMBER	LENGTH	NO. OF TEETH
195L050	19.5"	52	285L050	28.5"	76
210L050	21.0"	56	300L050	30.0"	80
225L050	22.5"	60	322L050	32.2"	84
240L050	24.0"	64	345L050	34.5"	86
255L050	25.5"	68			